

TECHNICAL DATA SHEET

Healix® XPP-MR

Circular PP from Maritime Ropes



Healix helps breaking the plastic wave by closing the loop on plastic fiber waste.

Used nets, ropes and other synthetic fiber-based plastics are collected and recycled into pristine circular polymers for the global manufacturing supply chain.



Product Characteristics

Healix® XPP-MR is a circular polyolefin (PO) grade supplied in pellet form. This 100% Post-Consumer Waste based grade, originating from maritime ropes, is characterized by moderate impact and stiffness and low residual odor. The material can vary in different dark colors, but not (carbon) black.

Recommended Applications

Healix® XPP-MR is a general-purpose grade that can be used in a wide variety of thermoforming and injection molding applications.

This product is not tested and therefore not validated for use in food, pharmaceutical, medical, or potable water applications.

Physical

Description	Unity	Typical value	Standard
Meltflow Index (230°C/2.16 kg)	g/10 min	3.5	ISO 1133-1
Density	kg/m ³	920	ISO 1183-1
Bulk Density	kg/m ³	540	ISO 60
Ash content	%	< 2.0	ISO 3451-1/A/600°C
Volatiles	%	< 1.0	ASTM D6980 @ 120°C
PE Content (DSC)	%	< 45	ISO 11357-3

Healix BV

Phone +31 651 366 391
info@healix.eco

XPP-MR / 04 2023



Healix gives no warranties and assumes no liability in respect of application, processing, use or reliance on. Any information provided by Healix does not release the user from the obligation to perform its own analysis to determine the suitability of the product for the intended process or application.

healix.eco